UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/586,106	10/19/2007	Jae-Sub Song	038779/314194	1748
826 7590 12/09/2009 ALSTON & BIRD LLP			EXAMINER	
2712 12 02 121.2	ERICA PLAZA	DAGLAWI, AMAR A		
	RYON STREET, SUIT NC 28280-4000	E 4000	ART UNIT	PAPER NUMBER
			2618	
			MAIL DATE	DELIVERY MODE
			12/09/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/586,106	SONG ET AL.
Office Action Summary	Examiner	Art Unit
	AMAR DAGLAWI	2618
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with the o	correspondence address
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING D.  Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication.  If NO period for reply is specified above, the maximum statutory period Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tir will apply and will expire SIX (6) MONTHS from a, cause the application to become ABANDONE	N. mely filed the mailing date of this communication. ED (35 U.S.C. § 133).
Status		
1) ■ Responsive to communication(s) filed on <u>09/0.</u> 2a) ■ This action is <b>FINAL</b> . 2b) ■ This 3) ■ Since this application is in condition for alloware closed in accordance with the practice under Expression in the practice of the p	action is non-final.  nce except for formal matters, pro	
Disposition of Claims		
4) ☐ Claim(s) 1-16 is/are pending in the application 4a) Of the above claim(s) is/are withdra 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-16 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/o	wn from consideration.	
9) The specification is objected to by the Examine 10) The drawing(s) filed on is/are: a) acc Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Ex	epted or b) objected to by the drawing(s) be held in abeyance. Se tion is required if the drawing(s) is ob	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:  1. Certified copies of the priority document 2. Certified copies of the priority document 3. Copies of the certified copies of the priority application from the International Bureau * See the attached detailed Office action for a list	es have been received. Es have been received in Applicat rity documents have been receive u (PCT Rule 17.2(a)).	ion No ed in this National Stage
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	4)	
Information Disclosure Statement(s) (PTO/SB/08)     Paper No(s)/Mail Date	5)  Notice of Informal F 6)  Other:	

Art Unit: 2618

#### **DETAILED ACTION**

### Response to Amendment

Claims 1-16 are pending in the current office action. The amendment has been entered.

#### Response to Arguments

- 1. Applicant's arguments filed on 09/03/2009 have been fully considered but they are not persuasive.
- 2. Applicant argues that with respect to claims 1 and 14 that among the limitations that Koh fails to teach or suggest are 1. Base station identifiers 2. Status information of the base stations 3. A Base station monitor for using first and second measurement values to calculate factors of the base stations after the measurement values are received by a radio communication module 4. A measured result modifier for using status information of the base station information database.
- 3. However, the Examiner respectfully disagrees and applies the broadest reasonable interpretation to the claims consistent with the specifications without reading limitations from the specifications into claims. The claims are given there broadest reasonable interpretation in light of the specification as it would be interpreted by one of ordinary skill in the art. See In re Am.Acad *of Sci. Tech. Ctr.*, 367 F.3d 1359, 1364[, 70 USPQ2d 1827] (Fed. Cir. 2004).
- 4. Koh teaches in Figs.1 and 2 a base station transceiver subsystem control processor for the controlling the base station. Koh also teaches a base station manager that performs testing, operation, maintenance and administration for the base station. The Examiner recognizes and a person of ordinary skill in the art understands

Art Unit: 2618

5. that a base station contains and identifier and in this case Koh teaches a base station manager that performs testing, operation, maintenance and administration for the base station and it is inherent in the system that base station contains an ID that defines a sequence of 48 bits. The first 48 bits take the values of the 24 bits of the operator ID in order and the following 24 bits are administered by the base station operator (see col.4, lines 39-67, col.5, lines 1-5). Furthermore, Koh teaches (col.3, lines 10-25) a method and a system that measures the standing wave ratio for the base station (providing status information of the base station) and the method comprises the steps of generating a test signal by using a given test terminal included in the base station and by transmitting the generated test signal to the reception antenna and measuring the strength of a forward signal and a reflect signal for the reception antenna and obtaining the difference between the strength of the forward signal and the strength of the reflect signal and calculating the standing wave ratio for the reception antenna. The BCP (base station transceiver subsystem control processor) performs the operation of measuring the VSWR. Koh further teaches adjusting a variable attenuator to make the strength of the forward signal equal to the strength of the reflected signal and calculating the standing wave ratio for the transmission antenna by using the strength of the adjusted signal. Koh further teaches a radio data module for transmitting in a radio data format to a remote device which is equivalent to the BCP (the base station transceiver subsystem control processor) for controlling the base station as taught by Koh (see col.4, lines 40-67, col.5, lines 1-5).

Art Unit: 2618

## Claim Rejections - 35 USC § 102

6. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 7. Claims 1-8, 10-16 are rejected under 35 U.S.C. 102(b) as being anticipated by Koh et al (US 6,289,216 B1).

With respect to claim 1, Koh teaches An antenna system monitor of a base station, comprising: a radio communication module for receiving radio data including a first measurement value and a second measurement value of the antenna system of the base station (Fig.1, abstract); a message parser for parsing the radio data to parse a base station identifier and measurement information (abstract, Fig.4, col.6, lines 39-67, col.7, lines 1-5); a base station information database for storing identifiers of base stations to be monitored, and status information of the base stations (fig.1, col.4, lines 43-67, col.5, lines 1-31); a base station monitor for using the first and second measurement values to calculate factors of the base stations; and a measured result modifier for using status information of the base station in- formation database corresponding to the base station identifier and modifying the calculated factors (col.5, lines 30-67, col.6, lines 39-67, col.7, lines 1-67, Fig.1

With respect to claim 2, Koh further teaches the first measurement value is a power of a progressive wave and the second measurement value is a power of a reflected wave (abstract, col.6, lines 39-67, col.7, lines 1-67, Fig.4)

- 8. With respect to claim 3, Koh further teaches the factor of the base station includes a transmitted voltage standing wave ratio and a received VSWR (abstract, col.6, lines 39-67, col.7, lines 1-67, Fig.4)
- 9. With respect to claim 4, Koh further teaches the radio data include a plurality of first measurement values and second measurement values, in- formation on a number of measurement times, information on an order of measurements, and a caller number (abstract, col.7, lines 55-67, Fig.4, Fig.5, col.8, lines 1-35)
- 10. With respect to claim 5, Koh further teaches the base station monitor comprises: a VSWR calculator for using the respective first measurement value and second measurement value to calculate a VSWR; data storage unit for storing the calculated counter for controlling a calculation number of the VSWR; and final VSWR calculator for outputting a final by the measured result modifier (abstract, col.6, lines 39-67, col.7, lines 1-67, Fig.1, Fig.4, col.8, lines 1-30)

With respect to claim 6, Koh further teaches the measured result modifier comprises • a eliminator for eliminating a maximum value and a minimum value from among the stored VSWRs; and an average calculator for calculating an average of the VSWRs (abstract, col.2, lines 25-67, col.3, lines 1-10, col.4, lines 40-67, col.5, lines 30-67)

Art Unit: 2618

With respect to claim 7, Koh further teaches the measured result modifier further comprises: a superimposed value searcher for searching for a superimposed value from among the VSWRs; and a weight assignor for assigning a weight to the maximum superimposed value according to a result provided by the superimposed value searcher (abstract, col.6, lines 39-67, col.7, lines 1-67, Fig.1, fig.4)

With respect to claim 8, Koh further teaches the measured result modifier uses base station information stored in the base station information database to increase or decrease the calculated averaged VSWR to thus perform mode (abstract, col.4, lines 40-67, col.5, lines 30-67, col.6, lines 39-67, col.7, lines 1-67, Fig.1, Fig.4).

With respect to claim 10, Koh teaches An antenna system measurer being installed in a plurality of base stations, measuring an antenna system of each base station, and reporting measured in- formation to a monitoring server, the antenna system measurer (Fig1, abstract, col.2, lines 25-67, col.3, lines 1-30) comprising: a first measurer for measuring a first measurement value of the antenna system (Fig.1, abstract); a second measurer for measuring a second measurement value of the antenna system (abstract, Fig.4, col.6, lines 39-67, col.7, lines 1-5); a radio data module for transmitting in a radio data format to a remote device (col.4, lines 40-67, col.5, lines 1-5) [the BCP (the base station transceiver subsystem control processor) is equivalent to the radio data module] and a base station identifier that corresponds with the antenna system (col.4, lines 40-67) [see comments above with respect to the identifier]; the first measurement value and the second measurement value (fig.1, col.4, lines 43-67, col.5, lines 1-31); and a controller for controlling a number of measurement times of the first

Application/Control Number: 10/586,106

Art Unit: 2618

measurement value and the second measurement value and radio data transmission (col.5, lines 30-67, col.6, lines 39-67, col.7, lines 1-67, Fig.1)

With respect to claim 11, Koh further teaches the first measurement value is a power of a progressive wave and the second measurement value is a power of a reflected wave (abstract, col.6, lines 39-67, col.7, lines 1-67, Fig.4)

With respect to claim 12, Koh further teaches the antenna measurer further comprises a frequency converter for converting a frequency of the second measurement value, the radio data module outputs a frequency of a predetermined power to a receive antenna when receiving an instruction for measuring the receive antenna, and the controller controls the frequency converter to convert a frequency of a power signal reflected from the receive antenna (abstract, col.2, lines 25-67, col.3, lines 1-10, col.4, lines 40-67, col.5, lines 30-67)

With respect to claim 13, Koh further teaches the radio data includes a short message service (SMS) message (abstract, col.2, lines 25-67, col.3, lines 1-10)

With respect to claim 14, Koh teaches A method for measuring and monitoring an antenna system of a base station in a mobile communication system, comprising: using an antenna system measurer installed in a base station antenna and measuring a power of a progressive wave and a power of a reflected wave (Fig1, abstract, col.2, lines 25-67, col.3, lines 1-30); transmitting information including measurement values and measurement times of the progressive wave and the reflected wave and base station identifiers in a radio data format to a monitoring server (abstract, Fig.4, col.6, lines 39-67, col.7, lines 1-5); allowing the monitoring server to receive the radio data,

Application/Control Number: 10/586,106

Art Unit: 2618

parse the message, and search information on the corresponding base station from a base station in formation database; using the transmitted measurement values to calculate a voltage standingwave ratio of the base station; and modifying the calculated VSWR according to searched base station information when modification is needed (col.5, lines 30-67, col.6, lines 39-67, col.7, lines 1-67, Fig.1)

Page 8

With respect to claim 15, Koh further teaches calculating the VSWR includes: eliminating a maximum value and a minimum value from among the calculated VSWRs; and calculating an average of the VSWRs without the maximum value and the minimum value (abstract, col.2, lines 25-67, col.3, lines 1-10, Fig.1, Fig..4).

With respect to claim 16, Koh further teaches calculating the VSWR includes: searching superimposed values from among the VSWRs and assigning a weight to a VSWR corresponding to the superimposed value (abstract, col.2, lines 25-67, col.3, lines 1-10, col.4, lines 40-67)

# Claim Rejections - 35 USC § 103

- 11. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 12. The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

Application/Control Number: 10/586,106

Art Unit: 2618

1. Determining the scope and contents of the prior art.

2. Ascertaining the differences between the prior art and the claims at issue.

Page 9

- 3. Resolving the level of ordinary skill in the pertinent art.
- 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.
- 13. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).
- 14. Claim 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over Koh (US 6,289,216 B1) in view of Abrams et al (US 7,127,220 B2).

Koh teaches all the limitations of claim 1 except for a display for displaying the calculated final a communication interface for transmitting the calculated final VSWR to an external device; and an alarm unit for generating an alarm signal when the final VSWR is greater than a predetermined threshold value which is taught in related art by Abrams (Fig.1, Fig.2, #122, col.3, lines 45-67, col.4, lines 1-45, abstract).

15. It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the teachings of Koh (the system) to incorporate the display of Abrams so as to display operating conditions such as forward power, reflected power VSWR.

Art Unit: 2618

#### Conclusion

16. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to AMAR DAGLAWI whose telephone number is (571)270-1221. The examiner can normally be reached on Monday- Friday (7:30 AM- 5:00 AM).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, NGUYEN DUC can be reached on 571-272-7503. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2618

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Amar Daglawi Examiner Art Unit 2618

/Amar Daglawi/ Examiner, Art Unit 2618

/Duc Nguyen/ Supervisory Patent Examiner, Art Unit 2618